

Certificate Of Conformity to EN14960:2019

This certificate relates only to the individual product detailed below. It confirms that at R the time of manufacture this product conforms to EN14960. To remain compliant this product must be tested annually.

To book your test please call +44 (0)1179 414 918 or visit www.airquee.com for more information.

This is the test certificate for your new inflatable. Please keep this in a safe place. This is valid for one year from the date below.

Product: 2 Part Energy Assault Course

Serial No: P49935\_B Code: AQ4937

Valid From: 06-12-2022 Certificate No: P49935\_B Tag No: 55500

Product Dimensions (m)											
Н	W	L									
3.3	3.1	12.3									
User Height (m)											
1	1.25	1.5	1.8								
Number of Users											
12	12	12	10								

	14g No: 35500						Number (	or users	
	Weight: Unit: 216kg Total: 235kg					12	12	12	10
	Structure					otes	***************************************		
	1 Security Of Seems	Х			Material : gloss 630g pvc			-	
	2 Stitching	X							
	3 Anchor Points	X			Anchor points: 16 pcs PVC & metal triangle Bottom				,
	4 Anchor Accessories	X			Supplied anchor accessories: 16 pcs / 400 mm* 18 r	mm metal peg	gs		
	5 Walls & Towers	X			Inside wall height: 1.75 m				
	6 Blower Tube(s) / Valve(s)	X			Blower tube length: 1.47 m Position: 2 pcs	s left side + 2	pcs right side		
	7 Zip(s)	X			Zips: 6 pcs (exterior velcro flap + interior non return	n flap)			
	8 Fabric Flame Retardant	Χ							
	9 Fabric Strength	X			3 3				
]	LO Step / Ramp Size	Χ			Platform height: 0.60 m Step depth: 1.00	m			χ
1	11 Grounding	X							
1	12 Sharp Angles	X							
- 1	13 Stability	X							
	L4 Ropes			X					
1	L5 Artwork			X					
1	L6 Air Loss Points	Х							
1	.7 Kilopascal (kPa)	X			kPa: 1.31 / 1.39				
1	L8 Fall Off Height (FOH)	Χ			FOH: 0.58 m				
1	.9 Trough Depth	Χ							
2	20 Thread	X			,				
2	21 Netting	Χ			Netting: black scrim fixed Roof : black glos	s 450g PVC			
2	22 Entrapment	X							
2	23 Deflation / Evacuation Time	Χ							0
2	24 Windows	Χ	-						
2	25 Markings	X							
2	26 Identification	X							
	Totally Enclosed Structures			Notes					
	27 Exits			X					
	28 Exit Markings			X					
	29 Lighting Supports			X					
	30 Emergency Lighting			X					
3	31 Deflation Speed			X					1
3	32 User Area Pressure			X					
	Slides			Notes					
	33 Wall Height / Platform Height	Χ			Wall height: 0.9 m Platform height: 2.35 n	n	-		
	34 Run-Out	X			Run out: 1.7 m				
	35 Clamber Step	Х			Width of slide: 1.8 m				
3	36 Slide Sheet	Χ			Slide sheet: red sliding material PVC				
	Blower				otes		-		
	37 Size & Type	Χ			Blower power: 2 pcs 1.5HP				
	88 Inlet & Outlet Mesh	Χ							
	9 Cable & Plug	Χ							
4	10 Casing & Impeller	Χ							
				1 1					

SIGNED BY: Deák Loránt RPII ANNUAL INFLATABLE INSPECTOR Airquee Ltd

41 Pat Test 42 Return Flap

Date of test: 23-11-2022

**Duel House** Llandowlais Street Cwmbran NP44 7XB, UK

Tel:+44 (0)1179 414 918

Email: sales@airquee.co.uk





To remain compliant this product must be tested annually.